

The following are products recently introduced to the concrete market as well as models which have undergone significant changes. For more information on any of these products, simply fill out the reader service card included in this issue.



## S 36 SX Pump

The S 36 SX with RZ4 boom from Schwing combines the features of a Roll and Fold and a 270° Z-tip section boom, allowing for concrete placement at distances of more than 118 ft. vertically and 105 ft. horizontally. Its patented Super X Outriggers provide fast setup and maximum horizontal reach. A standard low-maintenance, Generation 3 2025-5 120/80 MPS pump delivers up to 178 cu. yds. per hour. Additional features include a 740° slewing range, a 5-in. pipeline diameter and an unfolding height of 28 ft. 10 in.

Indicate 73 on card



## Mini R-Meter

The Mini R-Meter from James Instruments is a rugged, hand-held field instrument for finding the location, depth and size of reinforcement rebar, post tension, copper and conduit in place. The Mini R-Meter locates rebar up to 8 in., or 200 mm. Its features include an eddy current sensor design for greater accuracy and a single sensor for all depth ranges.

Indicate 74 on card

## Side Grader Attachment

The Komatsu-approved Side Grader excavator attachment from Sidewalk Grading Systems is designed to substantially reduce sidewalk prep costs while increasing productivity through reduced concrete overruns and easy maneuverability around utilities. It utilizes Topcon technology to produce a finished grade within  $\frac{3}{16}$  in., enabling concrete forms to be set directly on. The unit averages up to 2,000 ft. per day.

Indicate 75 on card



## Epoxy Floor Coating

UCoat Water-based Epoxy Floor Coating from UCoat It America is a commercial-grade epoxy floor coating for concrete and wood surfaces. The first coat is a bonding coat applied directly to a freshly prepared damp floor. A co-plastimer additive allows UCoat to flow and dry at the proper rate, penetrating the surface and permanently bonding to the substrate. It's free of noxious odors, and floors are ready for use after 24 hours.

Indicate 76 on card



## Hollow Kick Molding

Hollow Kick Molding from Boccia Bros. is a drainage system that directs water through the floor and into the footing drain pipe, eliminating the possibility of water accumulating on the floor. The molding is installed where the basement floor abuts the interior side of the foundation wall, creating a floating slab.

Indicate 77 on card



## Spray-on Liner

LINE-X's XS BK-100 is an all-purpose coating to protect long-term assets against impact, abrasion and corrosion. XS BK-100 does not stick to concrete and is an excellent product to spray on forms as it breaks away with just a tap and leaves your forms clean, reducing maintenance.

Indicate 78 on card

## Kestrel 4300 Construction Weather Tracker

The Kestrel 4300 Construction Weather Tracker from Nielsen-Kellerman has been customized for construction professionals who place concrete. The rugged, waterproof tool measures and stores the evaporation rate; relative humidity; current, maximum and average wind speed; temperature; dew point; barometric pressure; heat stress index; wet bulb temperature; wind chill; altitude; and density altitude. It also allows for data charting.

Indicate 79 on card

